

Huggy 42-V2<sup>TM</sup> Tent - UNICEF Standard



## Product key features Huggy 42-V2™ Tent

- UNICEF standard
- · Waterproof, rotproof and UV-stabilized
- Lightweight, rectangular and framed tent that can be used for schooling, storage or temporary shelter purposes (comes in three sizes)
- Outer tent fabric is made of 450 550 g/m2 PVC coated fabric, natural white
- Marking and logo customised to your requirements.

| Huggy 42-V2™ Tent       |
|-------------------------|
| Total size of 7 m x 6 m |

## Technical specifications

## Dimensions - Huggy 42-V2™ Tent

| Outer tent    |               |  |  |
|---------------|---------------|--|--|
| Total size    | 7.00 x 6.00 m |  |  |
| Centre height | 2.95 m        |  |  |
| Wall height   | 2.10 m        |  |  |
| Inner tent    |               |  |  |
| Centre height | 2.40 m        |  |  |
| Wall height   | 1.95 m        |  |  |

| Materials Control of the Control of |   |  |
|---|---|--|
| Outer tent  | 450 - 550 gsm fire retardant* PVC coated fabric 5000 mm, natural white  |  |
| Inner tent  | 120 gsm Polycotton, natural white   |  |
| Ground sheet  | 190 gsm Polyethylene (HDPE), PVC fabric, sewn in bathtub, light grey/natural white  |  |
| Windows   | Eight windows on long sidewalls 0.90 x 1.10 m with PVC stripes reinforcement / four windows on short sidewalls 0.85 x 1.00m with PVC stripes reinforcement  |  |
| Doors   | One door on each gable end side 1.20 x 2.00 m, closed with velcro   |  |
| Ground sheet  | Double stitched to inner tent, 100 - 200 mm above the ground  |  |
| Main frame  | 46 aluminum pipes 36.90 mm diameter, 2 mm thick, silver / 15 steel connectors 42 mm diameter, 2 mm thick, silver / 14 steel connectors with base plates 42 mm diameter, 2 mm thick, silver / five hanging steel connectors 8 mm diameter, two hooks on each end, silver |  |
| Seams   | All seams are double-stitched with welded main roof seams   |  |

## Packing & shipping

All contents are packed in a wooden box.

|                    | Package A   | Package B   |
|--------------------|---|---|
| Contents           | One roof, two wall and two door panels, one inner tent, 10 pcs 4 m ropes, two pcs 4.5 m ropes and instruction sheet | 46 frame pipes, 29 frame connectors, 12 pegs, five hanging connectors, 10 base plates, hammer, instruction sheet and repair kit |
| Weight per package | 125 kg  | 130 kg  |
| Total weight       | 255 kg  |   |
| Volume per package | 110 x 94 x 56 cm / 0.579 cbm  | 200 x 46 x 53 cm / 0.488 cbm  |
| Total volume       | 1.067 cbm   |   |

| Estimated loadability |               |  |  |
|-----------------------|---------------|--|--|
| Container             | Wooden crates |  |  |
| 20' GP container      | 24 tents      |  |  |
| 40' DC container      | 50 tents      |  |  |
| 40' HC container      | 55 tents      |  |  |